


WALL SAW WSE2226 ★★★

Cutting depths up to 1005 mm



Optimum torque and rotational speeds thanks to the innovative drive concept with 2-speed transmission



Extremely light and robust all-in-one blade guard for normal, corner and flush cutting



Cool water bypass for dry cutting

Developed for the toughest and most exacting applications thanks to a cutting depth of up to 1005 mm, which is unique worldwide, the WSE2226*** wall saw is particularly suitable for major cutting tasks. The pioneering P2® drive concept enables

the combination of extreme reliability and optimum performance with low service requirements and reduced service costs. The standard remote control enhances ease of use and safety in the workplace.

System & Accessories



Technical data

Saw blade	
Max. cutting depth	1005 mm
Max. saw blade Ø	2200 mm
Free detachable up to Ø	1025 mm
Blade flange mounting	Quick-release flange
Saw blade fixing (flush cuts)	6 countersunk head screws, 130 mm graduated circle
Electric motor	
Water-cooled high-frequency motor	
Output at 32 A	17 kW
Output at 63 A	26 kW
Control unit	
Spannung	400 V / 50 Hz
Frequenz	50 Hz
Gewicht	26 kg
Weight	
Wall Saw WSE2226*** incl. feed motors	26 kg
Electric main drive motor WSE2226***	25 kg
Blade guard 1200 mm All-In-One CL	22 kg

System & Accessories

Wall saw system WSE2226***	
10986600	Wall Saw WSE2226 incl. feed motors
10986800	Electric main drive motor WSE2226 400 V / 50 Hz
10986700	Electric control unit WSE2226 400 V / 50 Hz incl. radio remote control
10981719	Transport trolley
10989200	Blade guard 1200 mm All-In-One CL
10982079	VAS G Track / 1100 mm / alu
10981818	VAS G Track / 2200 mm / alu
977523	Track connector for VAS and VS tracks
965987	V-Track feet alu, flat
965987	V-Track feet alu, flat
965987	V-Track feet alu, flat
10980346	Tool box
Accessories	
977523	Track connector for VAS and VS tracks
10977882	Blade flange ST compl.
10989200	Blade guard 1200 mm All-In-One CL
10992730	Blade guard holder AIO/Alu 2 pcs.
10984099	Blade guard 800 mm 3 pcs.. All-In-One
10992724	Uptake AIO800 on WSE2226
10984100	Blade guard 1000 mm 3 parts. All-In-One
10992726	Uptake AIO1000 on WSE2226
10984101	Blade guard 1200 mm 3 parts All-In-One
10992727	Uptake AIO1200 on WSE2226
977606	Blade guard 1600 mm 2 parts
976184	Blade guard 2200 mm 2 parts
10992734	Uptake 1600/2200 2 parts on WSE2226
965987	V-Track feet alu, flat
961983	V-Swivel track feet
10977452	V-Rotary rail support compl.